

PRODUCT DATA SHEET

PTS 2202 Package API SN/CF

PRODUCT DESCRIPTION:

Is a high-performance requirement for the API SN categories and also meets GM dexos-1 in appropriate Group III BASE STOCK with 24 or 35 SSL. This additive system can be used in a variety of viscosity grades. The specification is cost-effective formulation.

GENERAL APPLICATIONS:

PTS 2202 package is developed premium multi-grade gasoline engine oils based on Group-II or Group-III base stock at economical treatrates. By design the package has a high BN, and BN can be boosted further by incorporated aBNBooster.

Performance Level, Meets & Exceeds	Treat Rate
API SN/CF, ILSAC GF-5, DEXOS 1 Chrysler MS 6395, Ford 6095M	8.9% mass

Technical Data Sheet			
Test	Test Method	Unit Result	
Appearance	Visual	Transparent brown liquid	
Kinematic, Viscosity at 100°C	ASTM D 445	mm ² /s	106
Density at 15°C	ASTM D 1298	kg/m ³	0.985
Flash Point	ASTM D 92	°C	210
Base Number	ASTM D 2896	mg KOH/g	98
Sulfated Ash	ASTM D 874	% mass	10.5
Calcium	ASTM D 4951	% mass	2.65
Phosphorus	ASTM D 4951	% mass	0.91

Note: The above values are not specifications and are provided to indicate the typical values measured on the products.

STORAGE AND HANDLING:

Recommended maximum blending temperature is 70°C. Store away from direct sunlight and keep sealed to avoid atmospheric condensation.