

PRODUCT DATA SHEET

PTS 2204 Package API SP

PRODUCT DESCRIPTION:

PTS 2204 Package is a high-performance requirement for the API SP categories and also meets GM dexos-1 in appropriate Group III BASE STOCK with 24 or 35 SSI. This additive system can be used in a variety of viscosity grades. The specification is cost-effective formulation.

GENERAL APPLICATIONS:

PTS 2204 Package is developed premium multi-grade gasoline engine oils based on Group-II or Group-III base stock at economical treatrates. By design the package has a high BN, and BN can be boosted further by incorporating a BNBooster.

Performance Level, Meets & Exceeds	Treat Rate
API SP, ILSAC GF-6, ACEA C2/C3/C5-16 MB 229.31, CHRYSLER MS6395, DEXOS 1 GEN 2, FORD	8.9% mass

Technical Data Sheet			
Test	Test Method	Unit Result	
Appearance	Visual	Transparent brown liquid	
Kinematic, Viscosity at 100°C	ASTM D 445	mm ² /s	98
Density at 15°C	ASTM D 1298	kg/m ³	0.985
Flash Point	ASTM D 92	°C	174
Base Number	ASTM D 2896	mg KOH/g	98
Sulfated Ash	ASTM D 874	% mass	9.82
Calcium	ASTM D 4951	% mass	2.15
Phosphorus	ASTM D 4951	% mass	0.86

Note: The above values are not specifications and are provided to indicate the typical values measured on the products.

STORAGE AND HANDLING:

Recommended maximum blending temperature is 70°C. Store away from direct sunlight and keep sealed to avoid atmospheric condensation.