

PXP48 Polymethacrylate (PMA) Pour Point Depressant

- **Product Introduction**

PXP48 is a polymethacrylate (PMA) type pour point depressant. It has excellent effect of pour point depressing and shear stability. Applicable to internal combustion engine oil, gear oil, hydraulic oil and other lubricating oils, is a general type of pour point depressant; It has a good pour point depressing effect for Group I, Group II and Group III base oils.

- **Product Quality Characteristics & Test Method**

Item	Index	Typical Value	Test Method
Appearance	Clear, transparent, no sediment liquid	Clear, transparent, no sediment liquid	Visual Inspection
Kinematic Viscosity (100°C), mm ² /s	300-600	390	ASTM D445
Flash Point (COC), °C	≥140	160	ASTM D92
Color, No.	<0.5	<0.5	ASTM D1500
Density (20°C), kg/m ³	800-950	900	ASTM D4052

- **Product Storage/Handling/Transportation/Package**

Packed in 200L iron drum with 170kg net weight or according to user's requirement, suitable for all means of transport.

For short-term storage and transportation, the temperature of the product shall not surpass 75°C; for long-term storage, it shall not surpass 45°C.

The product is offered with a guarantee period of 24 months, store in dry, cleaning, and ventilated warehouse. In case of accidental contact with skin, wash it off thoroughly with water and detergents.