

PTG 8010 PACKAGE

AUTOMOTIVE AND INDUSTRIAL GEAR OIL ADDITIVE

PRODUCT DESCRIPTION :

PTG 8010 Package is a balanced gear oil additive package when used along with appropriate base oils and viscosity modifiers is suitable to formulate automotive and Industrial gear lubricant. It contains Extreme pressure additives, rust and corrosion inhibitors, antiwear and antioxidant additives.

Features:

- Superior Extreme pressure performance.
- Excellent antiwear protection.
- Optimized anti-corrosion performance.
- Compatibility with different base oils.

Dosage:

4.4 wt% API GL-5, ZFTE-ML07A

2.2 wt% API GL-4

1.5 wt% AIST 224, AGMA 9005-E02, David Brown S1.53.101(E)

TECHNICAL DATA SHEET		
TEST	UNIT	RESULTS
Appearance		Clear Light Yellow To Slightly Hazy Amber Liquid
Specific gravity at 60°F (15.6 °C)		0.98
Pounds/gallon		8.17
Kinematic Viscosity at 100°C	cSt	3
Flash Point, COC, min	°C	70
Phosphorous, wt%	% mass	1.2
Sulfur, wt%	% mass	28

PETRAX MAKES NO EXPRESSED OR IMPLIED WARRANTIES ON MERCHANTABILITY, FITNESS OR OTHERWISE with respect to this product. In addition, while the information contained herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestions for use are made without guarantee inasmuch as conditions of use are beyond our control. The properties given are typical values and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes.