

PXAD 5555

DISPERSANT

PRODUCT DESCRIPTION :

PXAD 5555 is an ashless polymeric super dispersant designed to be used with additive packages in lubricant applications. It provides excellent low temperature sludge and varnish control in gasoline engines, and effective dispersancy and soot control in diesel engine, natural gas and marine cylinder lubricants.

APPLICATIONS :

PXAD 5555 can be used in the following applications:

- Engine oils
- Marine Lubricants
- Natural Gas engine oils
- Transmission fluids
- Gear oils for clean gear applications
- Industrial oils as an emulsifier in rock drill oils

DOSAGE :

Dosage will vary depending on the application from 0.05-5 wt% in finished oils.

TECHNICAL DATA SHEET		
TEST	UNIT	RESULTS
Appearance		Dark amber
Specific gravity at 60°F (15.6 °C)		0.91
Kinematic Viscosity at 100°C	cSt	400
Flash Point, COC, min	°C	160
Total Base Number		72
Nitrogen, wt%	%	3.1

HANDLING & STORAGE :

Maximum temperatures of 43°C (110°F) for handling and 38°C (100°F) for long-term storage are recommended. Typical precautions for handling concentrated chemicals and blending additives into base oils should be observed.

PETRAX MAKES NO EXPRESSED OR IMPLIED WARRANTIES ON MERCHANTABILITY, FITNESS OR OTHERWISE with respect to this product. In addition, while the information contained herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestions for use are made without guarantee inasmuch as conditions of use are beyond our control. The properties given are typical values and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes.