

PXP 49

A POLYMERIC CONCENTRATE DESIGNED TO BE USED AS A POUR POINT DEPRESSANT IN DIFFERENT LUBRICANTS

PRODUCT DESCRIPTION :

PXP 49 is a polymeric concentrate designed to be used as a pour point depressant in different lubricants. **PXP 49** displays excellent solubility in different base stocks and enables easier handling. It is effective in reducing pour point of waxy group I base oils.

APPLICATIONS:

PXP 49 can be used in the following applications:

- Engine oils (MRV, pour point for 10W's and 15W's)
- Hydraulic Oils (Pour Point)
- Gear Oils (Brookfield at -26°C and - 12°C)
- Metalworking Fluids And Greases

DOSAGE:

Dosage will vary depending on the application from 0.05-2 wt%.

TECHNICAL DATA SHEET

TEST	UNIT	RESULTS
Appearance		Light Amber Viscous Liquid
Specific gravity at 60°F (15.6 °C)		0.94
Pounds/gallon		7.42
Kinematic Viscosity at 100°C	cSt	>100
Flash Point, COC, min	°C	120
ASTM D1500, Color		0.5-2.5

HANDLING & STORAGE:

Maximum temperatures of 80°C (176°F) for handling and 38°C (100°F) for long-term storage are recommended. Typical precautions for handling concentrated chemicals and blending additives into base oils should be observed.

PETRAX MAKES NO EXPRESSED OR IMPLIED WARRANTIES ON MERCHANTABILITY, FITNESS OR OTHERWISE with respect to this product. In addition, while the information contained herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestions for use are made without guarantee inasmuch as conditions of use are beyond our control. The properties given are typical values and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes.