

PTS 2206 PACKAGE

HIGH-PERFORMANCE ADDITIVE PACKAGE

PRODUCT DESCRIPTION :

PTS 2206 is a balanced engine oil additive formulated to provide control of deposits, wear, rust, oil oxidation in gasoline engines. It is designed for use where Industry certification is not required. When used with appropriate base stocks and VII, it can produce high quality passenger car, motorcycle and diesel engine oils.

DOSAGE :

Varies depending on application and performance level desired.

TYPICAL PHYSICAL PROPERTIES:

TECHNICAL DATA SHEET		
TEST	UNIT	RESULTS
Appearance		Dark Amber Viscous Liquid
Specific gravity at 60°F (15.6 °C)		0.99
Pounds/gallon		8.26
Kinematic Viscosity at 100°C	cSt	120
Flash Point, COC, min	°C	160
Phosphorous, wt%	% mass	1.47
Nitrogen, wt%	% mass	0.83
Calcium, wt%	% mass	3.42
Zinc, wt%	% mass	1.65

HANDLING & STORAGE :

Maximum temperatures of 80°C (176°F) for handling and 38°C (100°F) for long-term storage are recommended. Typical precautions for handling concentrated chemicals and blending additives into base oils should be observed.

PETRAX MAKES NO EXPRESSED OR IMPLIED WARRANTIES ON MERCHANTABILITY, FITNESS OR OTHERWISE with respect to this product. In addition, while the information contained herein is believed to be reliable, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof. All recommendations or suggestions for use are made without guarantee inasmuch as conditions of use are beyond our control. The properties given are typical values and are not intended for use in preparing specifications. Users should make their own test to determine the suitability of this product for their own purposes.